

## TECHNICAL DATA SHEET



# EXTREME PRESSURE VALVE TRAIN RACING GREASE

PRODUCT # 10578

NLGI #1 GRADE

### TEST

### ASTM

### TYPICAL

### SPEC

**Thickener Type**

**Texture**

**Color**

**Penetration**

**0 Strokes @ 77°F**

**60 Strokes @ 77°F**

**Rust Prevention**

**Four Ball E.P. Test**

**Weld Point, Kg**

**Load Wear Index, Kg**

**Dropping Point, °F**

**Fragrance**

**Base Oil Viscosity**

**cSt @ 40°C**

**cSt @ 100°C**

**Lithium Complex**

**Smooth, Tacky**

**Aqua Blue**

**D-217**

**D-217**

**D-1743**

**D-2596**

**D-2265**

**D-445**

**D-445**

**319**

**319**

**Pass**

**620**

**109**

**496**

**Peppermint**

**336**

**22.0**

**310-340**

**310-340**

**Pass**

**200 Min**

**30 Min**

**428 Min**

**Lucas Extreme Pressure Valve Train Racing Grease is a heavily fortified lithium complex grease designed to provide protection under the most adverse racing conditions. Our grease has been proven in NHRA, NASCAR and Sprint Cars. It has excellent extreme pressure properties exceeding the minimum industry standards up to three times.**

**Our unique additive chemistry differentiates us from anything on the market today and provides the ultimate performance our customers come to expect from Lucas products.**